

DECLARATION OF PERFORMANCE

In accordance with Annex III of Registration (EU) No. 305/2011
(Construction Product Regulation)
Amended by commission Delegated Regulation (EU) No. 574/2014

1. Unique identification code of the product-type:
Pro Svum 05
2. Type, batch or serial number of any other element allowing identification of the construction product as required under article 11(4) of CPR
Batch no.: see product packing
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer after AVCP:
EN 1504-2 Surface protection systems for concrete, method 1.3, 2.2, 5.1, 6.1 and 8.2
EN 1504-3 Structural and non-structural repair, method 3.1, 7.1, and 7.2
4. Name, registered trade name or registered trademark and contact address of the manufacturer as required under article 11(5)
Pro-*Tex* A/S
Silkeborgvej 259
8700 Horsens
Denmark
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified under article 12(2)
Not relevant
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V
System 2+
7. In case of a declaration of performance concerning a construction product that is covered by a harmonized standard
The product is subject to in-plant production control
8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued
Not relevant

9 Declared performance

EN 1504-2

Essential Characteristics	Requirements	Harmonised technical Specification
Compressive strength	Class I: ≥ 35 MPa	EN 12190:1999
Adhesion strength	> 2.0 MPa	EN 1542:2000
Abrasion resistance	2970 mg/m ²	EN ISO 5470-1
Permeability	$S_D = 450$ m	EN 1062-6
Water vapour Permeability	1,8 m	EN ISO 7783-2
Capillary absorption for water	0,03 kg m ⁻² h ^{-0,5}	EN 1062-3
Freeze – thaw	Class R4	EN 13687-1
Impact resistance	4 NM	EN ISO 6272-1


EN 1504-3

Compressive strength	Class R3 $\geq (35$ MPa)	EN 12190
Chloride ion content	0,05 %	EN 1015-17
Adhesive strength	$\geq 2,0$ MPa	EN 1542
Frost – Thaw	Class R4	EN 13687-1
Capillary absorption	0,03 kg m ⁻² h ^{-0,5}	EN 1062-3

10 The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for the manufacturer and in name of the manufacturer by:

Place and date of Issue 03-03/2022



Kim Lorentsen

Pro-Tex A/S

Silkeborgvej 259
8700 Horsens
www.pro-tex.dk

telefon
+ 45 75 86 83 73

e-mail
info@pro-tex.dk